



Radiy delivers a digital I&C platform that is robust, flexible, and scalable. It provides state-of-the-art functions, services, and safeguards for both safety and non-safety applications in the nuclear industry. The RadICS product line consists of a Logic Module, basic input/output modules, and specialty modules all housed in a seismically qualified chassis.

The Discrete Outputs Module (DOM) serves as a high-density module providing for 32 independent, highly reliable, and optically isolated discrete outputs. The Logic Module uses the DOM to drive field devices, indicators, and other functions. The DOM also performs robust and continuous self-diagnostics to ensure the safety and integrity of each output and module function. In the event of critical failures, the DOM de-energizes to a safe-state.



## Discrete Outputs Module (DOM)

- High density 32 channel Form-A optically isolated, fuse and overvoltage protected discrete outputs.
- Independent FPGA for discrete output processing, self-diagnostics, and fail-safe functional behavior.
- IEC 61508 SIL 3 certification in single and multiple channel configurations.
- Robust self-diagnostics ensure higher reliability and early fault detection with safety-focused fault management.
- Segregation of output processing, self-diagnostics, and watchdog functions assures safety-critical functionality.
- Galvanic isolation for signal outputs with robust and dedicated communication links to Logic Module for secure data transfer.
- Inherent on-board diversity features eliminate common cause failure vulnerabilities.
- FPGA technology ensures resilience to obsolescence.



## Discrete Outputs Module Technical Specifications

<b>Output Channel Load Voltage / Current (maximum switching voltage / current)</b>	up to 48 VDC, 0.2 amp, Form A contact
<b>Output Channel Isolation</b>	all output channels are galvanic-isolated up to 500 V <sub>RMS</sub> AC or 707 VDC field- to-Chassis and channel-to-channel
<b>Output Channel Isolation Method</b>	optical relay
<b>Output Overvoltage Protection</b>	up to ±60 VDC/VAC continuous (using external protection elements installed in Chassis)
<b>Information Package Exchange Cycle</b>	5 milliseconds
<b>Diagnostic Package Exchange Cycle</b>	5 milliseconds
<b>LVDS Line Speed</b>	100 megabit/second
<b>LVDS Line Protocol</b>	proprietary protocol with integrity checking (CRC), galvanic-isolated Tx / Rx
<b>Fiber Optical Lines Speed</b>	100 megabit/second
<b>Self-Diagnostic Functions</b>	diverse watchdog unit, checksum analysis, active diagnostics with internal fault detection, hardware error detection, functionally diverse continuous self-diagnostic tests, power supply fault detection
<b>Power Supply / Consumption</b>	2 independent inputs – 24 (18 – 36) VDC / 0.4 amp
<b>Indications</b>	2 status LED indicators (RUN/FAULT) 4-character dot matrix symbol-indicator for providing current operational mode, service information, and error codes
<b>Operating Temperature</b>	0 to 60 °C (32 to 140 °F)
<b>Operating Humidity</b>	5 to 90% relative humidity, non-condensing

Research & Production  
Corporation Rادی  
29 Geroyiv Stalingrada Street,  
Kropyvnytskyi 25009, Ukraine  
inter.project@radiy.com  
www.radiy.com

*For more than 20 years Rادی has provided advanced instrumentation and control (I&C) solutions for nuclear power plant modernization and new build projects in the global market. Rادی's main I&C product, the RadICS I&C Platform, was developed specifically for use in nuclear power plants. It is the only FPGA-based I&C platform with a SIL 3 certification in a single channel configuration. Radics, a wholly owned LLC, provides delivery services for the RadICS I&C Platform for international markets to meet local regulatory requirements. Rادی also offers industrial control systems, electrical equipment, and reverse engineering services.*